

3 Shelf Service Carts With Standard Handle

Model SC - Rugged general use carts for transporting small packages, parts, & more

1,200 LB CAP* (*800 lb with Thermorubber casters)



Product Features:

- All welded construction (except casters).
- Durable **12 gauge steel shelves**, 3/16" thick angle corners, and 12 gauge caster mounts for long lasting use.
- Tubular handle with smooth radius bend for comfort and uniform appearance.
- Bolt on casters, 2 swivel & 2 rigid - for easy replacement.
- 1-1/2" shelf lips up for retention.
- Clearance between shelves - 12"
- Overall height - 35".
- Powder coated gray finish.

SPECIFICATIONS

WxL (in)	5" Casters Models			Wgt. (lbs)
	Urethane	Thermorubber	Steel	
18 x 24	SC124-U5	SC124-T5	SC124-L5	90
30	SC130-U5	SC130-T5	SC130-L5	102
36	SC136-U5	SC136-T5	SC136-L5	114
48	SC148-U5	SC148-T5	SC148-L5	134
24 x 30	SC230-U5	SC230-T5	SC230-L5	124
36	SC236-U5	SC236-T5	SC236-L5	138
48	SC248-U5	SC248-T5	SC248-L5	170
60	SC260-U5	SC260-T5	SC260-L5	200
72	SC272-U5	SC272-T5	SC272-L5	230
30 x 36	SC336-U5	SC336-T5	SC336-L5	164
48	SC348-U5	SC348-T5	SC348-L5	200
60	SC360-U5	SC360-T5	SC360-L5	238
72	SC372-U5	SC372-T5	SC372-L5	274
36 x 48	SC448-U5	SC448-T5	SC448-L5	232
60	SC460-U5	SC460-T5	SC460-L5	276
72	SC472-U5	SC472-T5	SC472-L5	320

Options:

- 2 wheel brakes on swivel casters - **Code B5**
- Floor lock - **Code F5**
- All swivel casters - **Code AS**
- Top shelf lips down (flush) - **Code FT**
- All shelves lips down (flush) - **Code FA**
- Vinyl matting on top shelf - **Code VM**
- Other heights available.

3 Shelf Vibration Reduction Carts (Pneumatic Casters)

Model LH - Transporter for items over irregular surfaces

1,200 LB CAPACITY



Product Features:

- All welded construction (except casters).
- Durable **12 gauge steel shelves**, 3/16" thick angle corners, and 12 gauge caster mounts for long lasting use.
- Tubular handle with smooth radius bend for comfort and uniform appearance.
- Bolt on casters, 2 swivel & 2 rigid - for easy replacement.
- 1-1/2" shelf lips up for retention.
- Clearance between shelves - 12"
- Overall height - 39".
- Powder coated gray finish.

SPECIFICATIONS

WxL (in)	8" Casters		Wgt.(lbs)
	Semi Models	Full Models	
24 x 30	LH230-Z8	LH230-N8	146
36	LH236-Z8	LH236-N8	162
48	LH248-Z8	LH248-N8	192
60	LH260-Z8	LH260-N8	222
72	LH272-Z8	LH272-N8	252
30 x 36	LH336-Z8	LH336-N8	186
48	LH348-Z8	LH348-N8	224
60	LH360-Z8	LH360-N8	260
72	LH372-Z8	LH372-N8	298
36 x 48	LH448-Z8	LH448-N8	254
60	LH460-Z8	LH460-N8	300
72	LH472-Z8	LH472-N8	344

Options:

- 2 wheel brakes on swivel casters - **Code BN**
- Floor lock - **Code F8 or FN**
- All swivel casters - **Code AS**
- Top shelf lips down (flush) - **Code FT**
- All shelves lips down (flush) - **Code FA**
- Ergonomic handle - **Code EH**
- Vinyl matting on top shelf - **Code VM**
- Other heights available.

Casters For Steel Carts

Jamco carts offer unique twin-hole pattern caster mounts that will accept casters with 1-3/4" x 3" & 3" x 3" bolt hole patterns (unless otherwise noted).

Wheel Characteristics

- Phenolic
 - Best rollability, high strength, hardest material.
- Rubber
 - Best if floor has debris, quieter roll.
- Polyurethane
 - Best if floor conditions vary, non-marking.
- Thermorubber
 - Gray non-marking, soft rubber for quietest roll and best floor protection.
- Steel (semi)
 - High shock and impact resistant.
- Full Pneumatic
 - Absorbs shock and vibration, quiet movement, best for uneven floors or transporting over ridges in floors or mezzazines. Requires periodic maintenance.
- Semi Pneumatic
 - Same as full pneumatic without maintenance of air.

Brakes

- Wing Brakes (Toe)
 - On swivel casters only, must be ordered with caster.
- Floor Lock
 - Mount is welded in place, makes models not returnable.

4 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U4	4 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	N/A	B4
T4	4 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	N/A	B4

5 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U5	5 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	F5	B5
T5	5 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	F5	B5
L5	5 x 1-1/4	1-3/4 x 3	Steel (semi)	Plain	1,200 lbs	F5	B5

7 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P7	5 x 2	3 x 3	Phenolic	Roller	4,000 lbs	F7	B7
R7	5 x 2	3 x 3	Rubber (Mold-on)	Roller	1,800 lbs	F7	B7
U7	5 x 2	3 x 3	Polyurethane	Roller	3,000 lbs	F7	B7
T7	5 x 2	3 x 3	Thermorubber	Roller	2,000 lbs	F7	B7
L7	5 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F7	B7

6 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P6	6 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F6	B6
R6	6 x 2	3 x 3	Rubber (Mold-on)	Roller	2,000 lbs	F6	B6
U6	6 x 2	3 x 3	Polyurethane	Roller	3,600 lbs	F6	B6
T6	6 x 2	3 x 3	Thermorubber	Roller	2,200 lbs	F6	B6
L6	6 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F6	B6

8 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P8	8 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F8	B8
R8	8 x 2	3 x 3	Rubber (Mold-on)	Roller	2,400 lbs	F8	B8
U8	8 x 2	3 x 3	Polyurethane	Roller	3,800 lbs	F8	B8
T8	8 x 2	3 x 3	Thermorubber	Roller	2,400 lbs	F8	B8
L8	8 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F8	B8

N Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
N8	8 x 3	3 x 3	Full Pneumatic	Roller	1,200 lbs	FN	BN
N1	12 x 4	3 x 3	Full Pneumatic	Ball	2,200 lbs	N/A	N/A
Z8	8 x 3	3 x 3	Semi Pneumatic	Ball	2,000 lbs	F8	BN

Mill Duty Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
MP	8 x 2-1/2	3 x 3	Phenolic	Ball	7,000 lbs	ML	BM
MS	8 x 2-1/2	3 x 3	Steel	Ball	7,000 lbs	ML	BM

Floor Lock



4 Series



Urethane Thermorubber

5 Series



Urethane Thermorubber



Steel
7, 6, & 8 Series




Phenolic Mold On Rubber



Urethane Thermorubber



Steel
N Series



Full Pneumatic Semi Pneumatic

Mill Duty Series



Phenolic Steel