

2 Shelf 2,400 lb Reinforced Low Profile Carts

Model SX - Extra durable carts for heavy items

2,400 LB CAP.*(*2,000 lb with Rubber casters)



Options:

- 2 wheel brakes on swivel casters - **Code B6**
- All swivel casters - **Code AS**
- Floor lock - **Code F6**
- Bottom shelf lips down (flush) - **Code FB**
- Lockable drawer 5"h x 16"w x 16"d with 2 keys - **Code DS**
- Vinyl matting on top shelf - **Code VM**

Product Features:

- All welded construction (except casters).
- Durable **12 gauge steel shelves with under bracing**, 3/16" thick angle corners, and 12 gauge caster mounts for long lasting use.
- **Raised offset handle** (12" above top shelf).
- Bolt on casters, 2 swivel & 2 rigid, for easy replacement.
- 1-1/2" shelf lips down (flush) on top shelf and lips up on bottom shelf.
- Clearance between shelves - 17".
- Top shelf height - 28".
- Powder coated gray finish.

SPECIFICATIONS

WxL (in)	6" Casters Models			Wgt. (lbs)
	Phenolic	Rubber	Urethane	
24 x 30	SX230-P6	SX230-R6	SX230-U6	122
36	SX236-P6	SX236-R6	SX236-U6	134
48	SX248-P6	SX248-R6	SX248-U6	156
60	SX260-P6	SX260-R6	SX260-U6	178
72	SX272-P6	SX272-R6	SX272-U6	200
30 x 36	SX336-P6	SX336-R6	SX336-U6	152
48	SX348-P6	SX348-R6	SX348-U6	178
60	SX360-P6	SX360-R6	SX360-U6	206
72	SX372-P6	SX372-R6	SX372-U6	232
36 x 48	SX448-P6	SX448-R6	SX448-U6	200
60	SX460-P6	SX460-R6	SX460-U6	232
72	SX472-P6	SX472-R6	SX472-U6	264

2 Shelf 4,800 lb Reinforced Low Profile Carts

Model SW - Super heavy duty carts for heavy items

4,800 LB CAPACITY



Options:

- 2 wheel brakes on swivel casters - **Code B8**
- Floor Lock - **Code F8**
- Bottom shelf lips down (flush) - **Code FB**
- Lockable drawer 5"h x 16"w x 16"d with 2 keys - **Code DS**
- Vinyl matting on top shelf - **Code VM**

Product Features:

- All welded construction (except casters).
- Durable **12 gauge steel shelves with extra under bracing**, 3/16" thick angle corners, and 12 gauge caster mounts for long lasting use.
- **Raised offset handle** (12" above top shelf).
- Bolt on casters, 2 swivel & 2 rigid, for easy replacement.
- 1-1/2" shelf lips down (flush) on top shelf and lips up on bottom shelf.
- Clearance between shelves - 17".
- Top shelf height - 30".
- Powder coated gray finish.

SPECIFICATIONS

WxL (in)	8" Casters Models	Wgt. (lbs)	
	Phenolic		
24 x 30	SW230-P8	134	
36	SW236-P8	148	
48	SW248-P8	176	
60	SW260-P8	204	
72	SW272-P8	234	
30 x 36	SW336-P8	166	
	48	SW348-P8	198
	60	SW360-P8	232
	72	SW372-P8	264
36 x 48	SW448-P8	220	
	60	SW460-P8	258
	72	SW472-P8	296

Casters For Steel Carts

Jamco carts offer unique twin-hole pattern caster mounts that will accept casters with 1-3/4" x 3" & 3" x 3" bolt hole patterns (unless otherwise noted).

Wheel Characteristics

- Phenolic
 - Best rollability, high strength, hardest material.
- Rubber
 - Best if floor has debris, quieter roll.
- Polyurethane
 - Best if floor conditions vary, non-marking.
- Thermorubber
 - Gray non-marking, soft rubber for quietest roll and best floor protection.
- Steel (semi)
 - High shock and impact resistant.
- Full Pneumatic
 - Absorbs shock and vibration, quiet movement, best for uneven floors or transporting over ridges in floors or mezzazines. Requires periodic maintenance.
- Semi Pneumatic
 - Same as full pneumatic without maintenance of air.

Brakes

- Wing Brakes (Toe)
 - On swivel casters only, must be ordered with caster.
- Floor Lock
 - Mount is welded in place, makes models not returnable.

4 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U4	4 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	N/A	B4
T4	4 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	N/A	B4

5 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U5	5 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	F5	B5
T5	5 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	F5	B5
L5	5 x 1-1/4	1-3/4 x 3	Steel (semi)	Plain	1,200 lbs	F5	B5

7 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P7	5 x 2	3 x 3	Phenolic	Roller	4,000 lbs	F7	B7
R7	5 x 2	3 x 3	Rubber (Mold-on)	Roller	1,800 lbs	F7	B7
U7	5 x 2	3 x 3	Polyurethane	Roller	3,000 lbs	F7	B7
T7	5 x 2	3 x 3	Thermorubber	Roller	2,000 lbs	F7	B7
L7	5 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F7	B7

6 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P6	6 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F6	B6
R6	6 x 2	3 x 3	Rubber (Mold-on)	Roller	2,000 lbs	F6	B6
U6	6 x 2	3 x 3	Polyurethane	Roller	3,600 lbs	F6	B6
T6	6 x 2	3 x 3	Thermorubber	Roller	2,200 lbs	F6	B6
L6	6 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F6	B6

8 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P8	8 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F8	B8
R8	8 x 2	3 x 3	Rubber (Mold-on)	Roller	2,400 lbs	F8	B8
U8	8 x 2	3 x 3	Polyurethane	Roller	3,800 lbs	F8	B8
T8	8 x 2	3 x 3	Thermorubber	Roller	2,400 lbs	F8	B8
L8	8 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F8	B8

N Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
N8	8 x 3	3 x 3	Full Pneumatic	Roller	1,200 lbs	FN	BN
N1	12 x 4	3 x 3	Full Pneumatic	Ball	2,200 lbs	N/A	N/A
Z8	8 x 3	3 x 3	Semi Pneumatic	Ball	2,000 lbs	F8	BN

Mill Duty Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
MP	8 x 2-1/2	3 x 3	Phenolic	Ball	7,000 lbs	ML	BM
MS	8 x 2-1/2	3 x 3	Steel	Ball	7,000 lbs	ML	BM

Floor Lock



4 Series



Urethane Thermorubber

5 Series



Urethane Thermorubber



Steel

7, 6, & 8 Series



Phenolic Mold On Rubber



Urethane Thermorubber



Steel

N Series



Full Pneumatic Semi Pneumatic

Mill Duty Series



Phenolic Steel