

1, 2 & 3 Shelf Mesh Security Trucks

Models VA, VB, VC - Heavy duty secured cart with visual sides

2,000 LB CAPACITY



Model VA Shown

3,000 LB CAPACITY*
(*2,000 lb with rubber casters)



Model VB Shown

3,000 LB CAPACITY*
(*2,000 lb with rubber casters)



Model VC Shown

Product Features:

- All welded construction (except casters).
- **Four sides flattened 13 gauge expanded mesh 4' high and top cover.**
- **2 flattened 13 gauge expanded mesh doors on one side with lockable hasp** (padlock not included).
- Durable **12 gauge steel shelves**, 3/16" thick angle corners, and 12 gauge caster mounts for long lasting use.
- Tubular handle with smooth radius bend for comfort and uniform appearance.
- Bolt on casters, 2 swivel & 2 rigid, for easy replacement.
- Shelf lips down (flush).
- Clearance between shelves:
 - Model VA - 46"
 - Model VB - 22"
 - Model VC - 15"
- Overall height - 57".
- Powder coated gray finish.

Options:

- 2 wheel brakes on swivel casters - **Code B6**
- Floor lock - **Code F6**
- Ergonomic handle - **Code EH**
- All sides flattened 13 gauge expanded mesh 5' high - **Code SF**
- Fork lift pockets - 3" x 6" (specify center line) - **Code FP**

Model VA - 1 Shelf

DxW (in)	6" Casters Models			Wgt. (lbs)
	Phenolic	Rubber	Urethane	
24 x 48	VA248-P6	VA248-R6	VA248-U6	230
60	VA260-P6	VA260-R6	VA260-U6	266
30 x 48	VA348-P6	VA348-R6	VA348-U6	256
60	VA360-P6	VA360-R6	VA360-U6	290
36 x 48	VA448-P6	VA448-R6	VA448-U6	276
60	VA460-P6	VA460-R6	VA460-U6	314
72	VA472-P6	VA472-R6	VA472-U6	346

Note: Doors add 4" to width

Model VB - 2 Shelves

DxW (in)	6" Casters Models			Wgt. (lbs)
	Phenolic	Rubber	Urethane	
24 x 48	VB248-P6	VB248-R6	VB248-U6	274
60	VB260-P6	VB260-R6	VB260-U6	314
30 x 48	VB348-P6	VB348-R6	VB348-U6	306
60	VB360-P6	VB360-R6	VB360-U6	350
36 x 48	VB448-P6	VB448-R6	VB448-U6	338
60	VB460-P6	VB460-R6	VB460-U6	386
72	VB472-P6	VB472-R6	VB472-U6	430

Note: Doors add 4" to width

Model VC - 3 Shelves

DxW (in)	6" Casters Models			Wgt. (lbs)
	Phenolic	Rubber	Urethane	
24 x 48	VC248-P6	VC248-R6	VC248-U6	318
60	VC260-P6	VC260-R6	VC260-U6	368
30 x 48	VC348-P6	VC348-R6	VC348-U6	360
60	VC360-P6	VC360-R6	VC360-U6	414
36 x 48	VC448-P6	VC448-R6	VC448-U6	400
60	VC460-P6	VC460-R6	VC460-U6	462
72	VC472-P6	VC472-R6	VC472-U6	520

Note: Doors add 4" to width

Casters For Steel Carts

Jamco carts offer unique twin-hole pattern caster mounts that will accept casters with 1-3/4" x 3" & 3" x 3" bolt hole patterns (unless otherwise noted).

Wheel Characteristics

- Phenolic
 - Best rollability, high strength, hardest material.
- Rubber
 - Best if floor has debris, quieter roll.
- Polyurethane
 - Best if floor conditions vary, non-marking.
- Thermorubber
 - Gray non-marking, soft rubber for quietest roll and best floor protection.
- Steel (semi)
 - High shock and impact resistant.
- Full Pneumatic
 - Absorbs shock and vibration, quiet movement, best for uneven floors or transporting over ridges in floors or mezzazines. Requires periodic maintenance.
- Semi Pneumatic
 - Same as full pneumatic without maintenance of air.

Brakes

- Wing Brakes (Toe)
 - On swivel casters only, must be ordered with caster.
- Floor Lock
 - Mount is welded in place, makes models not returnable.

4 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U4	4 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	N/A	B4
T4	4 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	N/A	B4

5 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
U5	5 x 1-1/4	1-3/4 x 3	Polyurethane	Ball	1,200 lbs	F5	B5
T5	5 x 1-1/4	1-3/4 x 3	Thermorubber	Ball	800 lbs	F5	B5
L5	5 x 1-1/4	1-3/4 x 3	Steel (semi)	Plain	1,200 lbs	F5	B5

7 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P7	5 x 2	3 x 3	Phenolic	Roller	4,000 lbs	F7	B7
R7	5 x 2	3 x 3	Rubber (Mold-on)	Roller	1,800 lbs	F7	B7
U7	5 x 2	3 x 3	Polyurethane	Roller	3,000 lbs	F7	B7
T7	5 x 2	3 x 3	Thermorubber	Roller	2,000 lbs	F7	B7
L7	5 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F7	B7

6 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P6	6 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F6	B6
R6	6 x 2	3 x 3	Rubber (Mold-on)	Roller	2,000 lbs	F6	B6
U6	6 x 2	3 x 3	Polyurethane	Roller	3,600 lbs	F6	B6
T6	6 x 2	3 x 3	Thermorubber	Roller	2,200 lbs	F6	B6
L6	6 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F6	B6

8 Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
P8	8 x 2	3 x 3	Phenolic	Roller	4,800 lbs	F8	B8
R8	8 x 2	3 x 3	Rubber (Mold-on)	Roller	2,400 lbs	F8	B8
U8	8 x 2	3 x 3	Polyurethane	Roller	3,800 lbs	F8	B8
T8	8 x 2	3 x 3	Thermorubber	Roller	2,400 lbs	F8	B8
L8	8 x 2	3 x 3	Steel (semi)	Roller	4,000 lbs	F8	B8

N Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
N8	8 x 3	3 x 3	Full Pneumatic	Roller	1,200 lbs	FN	BN
N1	12 x 4	3 x 3	Full Pneumatic	Ball	2,200 lbs	N/A	N/A
Z8	8 x 3	3 x 3	Semi Pneumatic	Ball	2,000 lbs	F8	BN

Mill Duty Series

Code	Size (in)	Bolt Hole Pattern (in)	Wheel Material	Bearing	Capacity (set of 4)	Floor Locks	Brake Locks
MP	8 x 2-1/2	3 x 3	Phenolic	Ball	7,000 lbs	ML	BM
MS	8 x 2-1/2	3 x 3	Steel	Ball	7,000 lbs	ML	BM

Floor Lock



4 Series



Urethane Thermorubber

5 Series



Urethane Thermorubber



Steel

7, 6, & 8 Series



Phenolic

Mold On Rubber



Urethane

Thermorubber



Steel

N Series



Full Pneumatic

Semi Pneumatic

Mill Duty Series



Phenolic

Steel