



Hefti-Lifts

The Hefti-Lift units provide reliable powerful lifting when moving and positioning loads. The manual hydraulic foot pump yields $\frac{3}{4}$ " of platform travel per stroke, auto-shift models feature a two speed foot pump. The units roll smoothly on two (2) rigid and two (2) swivel poly-on-steel casters with foot operated brake. The units are designed of welded steel construction with platform uprights (except HYD-10-DA-SS). Each fork is $4\frac{1}{2}$ "W x $2\frac{1}{2}$ "H, the fork length is the same as the platform length. Overall fork width is 22". Not for use with pallets.

Stainless Steel units are compact, lightweight, and capable of turning in a small radius when space is limited. A built-in automatic load check valve is included for improved safety. Model HYD-5-SS features a hydraulic foot pump, while model HYD-10-DA-SS comes with a dual acting manual hydraulic hand pump.

Air Powered units are great in manufacturing or distributing facilities when space is limited. The single speed foot pump and hand held push button control (reciprocating air/oil power) raise forks to the desired location. The foot pump can be utilized to maneuver the table height to a precise position. Air powered units require a minimum hose diameter of $\frac{1}{4}$ " and air pressure of 72 to 100 psi.

MODEL NUMBER	PLATFORM SIZE (W x L)	SERVICE RANGE	UNIFORM CAPACITY	OPERATION	WEIGHT (POUND)
HYD-3	23" x 24"	3½" to 35"	880 lb.	FOOT PUMP	190
HYD-5	23" x 24"	4" to 44"	880 lb.	FOOT PUMP	246
HYD-10	23" x 24"	4" to 59"	880 lb.	FOOT PUMP	280
HYD-15	23" x 31½"	4" to 63"	1,500 lb.	FOOT PUMP	479
EXTENDED LENGTH					
HYD-5-EP	23" x 40"	3½" to 44"	400 lb.	FOOT PUMP	293
HYD-10-EP	23" x 40"	3½" to 59"	300 lb.	FOOT PUMP	308
AUTO-SHIFT					
HYD-5-AS	23" x 24"	4" to 44"	880 lb.	TWO-SPEED FP	251
HYD-10-AS	23" x 24"	4" to 59"	880 lb.	TWO-SPEED FP	286
PARTIALLY STAINLESS STEEL					
HYD-5-PSS	21" x 24"	3½" to 45½"	450 lb.	FOOT PUMP	236
STAINLESS STEEL					
HYD-5-SS	23⅞" x 21¼"	3½" to 45½"	450 lb.	FOOT PUMP	230
HYD-10-DA-SS*	N/A	3⅞" to 59"	800 lb.	HAND PUMP	270
AIR POWERED					
HYD-5-AIR	23" x 24"	3½" to 44"	880 lb.	AIR	261
HYD-10-AIR	23" x 24"	3½" to 59"	880 lb.	AIR	295

*OVERALL FORK WIDTH 22", LENGTH 25½"

DC Powered Hefti-Lifts

DC powered portable hydraulic lifts are user friendly providing reliable, powerful lifting when moving and positioning loads. Ideal for working in confined spaces and eliminates manual handling problems and injuries. Includes removable platform for operations requiring forks (except HYD-CB-10-DC). Not for use with pallets. Each fork is $4\frac{1}{2}$ "W x $2\frac{1}{2}$ "H, the fork length is the same as the platform length. Overall fork width is 22". Units roll easily on two (2) rigid and two (2) swivel poly-on-steel casters and include a foot operated brake. All welded steel construction with platform and uprights. Units are powered by one (1) 12V battery. Includes battery charger, battery charge indicator and emergency on/off switch. Attachments available.

304 stainless steel unit are ideal for food, pharmaceutical, chemical and clean room applications. Unit rolls easily on (2) two rigid and (2) two total lock swivel casters.

MODEL NUMBER	PLATFORM SIZE (W x L)	SERVICE RANGE	UNIFORM CAPACITY	POWER	WEIGHT (POUND)
HYD-10-DC	22⅞" x 25¾"	3½" to 59"	880 lb.	12V DC	330
HYD-CB-10-DC*	N/A	2¾" to 55½"	550 lb.	12V DC	566
STAINLESS STEEL HEFTI-LIFT					
HYD-10-DC-SS	22" x 25¾"	3½" to 59"	880 lb.	12V DC	257
ATTACHMENT OPTIONS					
HYDC-SPIN	SINGLE SPINDLE				10
HYDC-DSPIN	DOUBLE SPINDLE				18
HYDC-VFRK	V-SHAPE FORK				28
HYDC-RP	ROLLER PLATFORM				44
HYDC-BTP	BALL TRANSFER PLATFORM				34
HYDC-SSP	304 STAINLESS STEEL PLATFORM				22
HYDC-VBLK	V BLOCK				27
HYDC-RR	RUBBER ROLLER				22
HYDC-FRKHK	FORK HOOK				15

*OVERALL FORK WIDTH 22", LENGTH 25¾"